



Nacional

SAFETY VALVES



Safety valve Model 64

Safety valve 90° angular type of rapid opening (pop action), full nozzle, and spring loaded, adjusting ring, conventional or balanced.

Sizes :
from 1" x 2" up to 12" x 16"

Flanges rating:
Inlet 150 ÷ 2500#
Outlet 150 ÷ 300#
Also supplied with DIN flanges.

Safety valve Model 3-51

Safety valve 90° angular type of rapid opening (pop action), full nozzle, and spring loaded, adjusting ring, conventional or balanced.

Sizes :
from 1/2" x 3/4" up to 1" x 1"

Flanges rating:
Inlet 150 ÷ 1500#
Outlet 150 ÷ 300#, ASME 16,5
Supplied with DIN flanges under request



Model 3-5111 Flange

Model 3-5111 Threaded

Safety valve Model 3-50

Safety valve 90° angular type of rapid opening (pop action), full nozzle, spring loaded, adjusting ring.

Sizes :
from 1/2" x 3/4" up to 1" x 1"

Thread connections:
NPTF-ANSI B1.20.3; BSP-BS 21



Model 3-50



Model 3-5500

Safety valve Model 3-55

Safety valve 90° angular type of rapid opening, semi nozzle, spring loaded.

Sizes :
DN20x32 up to DN150xDN250


Flanges rating:
Inlet PN-16 ÷ 40
Outlet PN-16
Also supplied with ANSI B-16,5 flanges

Valve Silencer

Silencers are used to reduce noise in safety valves (PSV), Relief Valves (PRV), starter valves, blow valves, blow downs, ejectors, and discharge tanks.

Sizes :
Inlet size NPS 2 – 40

End Connection :
ASME B-16,5 flanges
ASME B-16,25 butt-welded



Silencer



Represent By :